



Tractors Built for the Best™

K range

Tractors for specialists



Carraro

K range



Alongside the well-established Agricube line, Carraro Tractors is now strengthening its presence on the special tractors market with the introduction of the new K range of compact, streamlined models.

With three versions - K4, K5 and K6 - with rear semi-folding protection roll bar and 35hp, 47hp or 55hp engine (Cummins licence in stage IIIA and IIIB), the new K range stands out for its excellent manoeuvrability and optimum comfort. These characteristics enable a notable improvement in the operator's work, and therefore significant benefits in terms of productivity.

The compact dimensions of the new K range vehicles, combined with the weight and steering angle characteristics, ensure particularly agile use without compromising the excellent lifting capacity (1500kg). A further feature is the dual hydraulic pump system (33.6 + 18 l/min for the K4, and 42 + 19 l/min for the K5 and K6).

The operator's position has been designed with a careful eye to ergonomics, and features a tilting steering wheel as standard: the result is comfortable, pleasant driving. Thanks to the platform design, the commands - from levers to pedals - are arranged to be within easy reach: everything is easy to access and extremely user-friendly.

The soft feel of the levers is another factor that makes for a pleasant driving experience thanks also to the transmission, with synchronised mechanical reverser, synchronised gears, 12 forward plus 12 reverse and 3 ranges.

The ground clearance varies from 322mm to 390mm, so work is not hindered even with dense thicket or on rough ground.

These new models are aimed not only at the professionals, who will find the perfect addition to their highly specialised tractors, but also those dealing with basic everyday work from transport to treatment, without having to forgo comfort, quality and reliability.

	Carraro K4	Carraro K5	Carraro K6
VERSION			
Rear semi-folding protection roll bar	yes	yes	yes
Tiltable steering wheel	yes	yes	yes
ENGINE			
Trademark	Kukje	Kukje	Kukje
Issue	EURO IIIA	EURO IIIA	EURO IIIB
Power (hp/kW)	35 / 26	47 / 35	55 / 40
Nominal speed	2600	2600	2600
Cooling	Liquid	Liquid	Liquid
Suction	Natural	Natural	Turbo
Engine capacity (cc./no. cyl.)	1714 / 3	2286 / 4	2286 / 4
Number of cylinders	3	4	4
Muffler	Horizontal	Horizontal	Horizontal
Tank capacity	45 l	45 l	45 l
TRANSMISSION			
Type	Mech.	Mech.	Mech.
Reverser	Synchro	Synchro	Synchro
Gears	12 + 12	12 + 12	12 + 12
Speed	30 km/h	30 km/h	30 km/h
DIFF LOCK coupling	Mech.	Mech.	Mech.
4RM coupling	Mech.	Mech.	Mech.
REAR LIFTER			
Type	Mech.	Mech.	Mech.
Strain control	yes	yes	yes
Lifting capacity	1500 kg	1500 kg	1500 kg
DISTRIBUTORS AND PUMPS			
Distributors	2 DE	2 DE	2 DE
Distributor outlets	4	4	4
Pump capacity (l/min)	33,6 + 18	42 + 19	42 + 19
REAR PDF			
PDF speed	540 / 540E	540 / 540E	540 / 540E
PDF coupling	EH	EH	EH
BRAKES			
Type	Multi-disc (oil bath)	Multi-disc (oil bath)	Multi-disc (oil bath)
WHEELS			
Front	7 - 16	9.5 - 16	9.5 - 16
Rear	12.4 - 24	13.6 - 26	13.6 - 26
DIMENSIONS			
Length	3316 mm	3316 mm	3316 mm
Wheelbase	1806 mm	1806 mm	1806 mm
Ground clearance	345 mm	399 mm	399 mm
Max overall	1450 mm	1540 mm	1540 mm
Weight	1655 kg	1742 kg	1742 kg
MISCELLANEOUS			
Ballast - 6 x 17.4 kg (tot. 104.4 kg)	yes	yes	yes
Maintenance kit (spanners, oil filter, grease nipple)	yes	yes	yes



Carraro SpA

Via Olmo, 37
35011 Campodarsego
Italy
Tel. +39 049 9219111
Fax +39 049 9289111

**Carraro Tractors
Service & Support**

Viale del lavoro, 1
45100 Rovigo
Italy
Tel. +39 0425 403611
Fax +39 0425 403674

**Carraro Tractors
Sales & Engineering**

Via Trentino, 4/6
35043 Monselice
Italy
Tel. +39 0429 1709111
Fax +39 049 9289271

info@carrarotracors.com

The information in this publication is provided for purely illustrative purposes; the manufacturer reserves the right to modify the models described without prior notice.

Drawings and photographs may refer to optional equipment or special options for other countries. For all other information, contact our sales network.