

ENGINE	FPT NEF, EURO IIIa
Maximum power ISO kW/hp	74 kW / 100.6 hp
Displacement and number of cylinders	4500 cc / 4 turbo intercooler
TRANSMISSION	
24 + 24 24 forward gears 24 reverse gears	Reverser: Mechanical • Hi-Lo: Synchro • Gear levers: Lateral • Gearbox: 4 gear synchro • Range: 3 gear range L/M/Hi synchro Tractor speed: 40 km/h Minimum speed of tractor: 0.5 km/h
24 + 12 FWD-REV 24 forward gears 12 reverse gears	Reverser: Electro-hydraulic • Hi-Lo: Electro-hydraulic • Gear levers: Lateral • Gearbox: 4 gear synchro • Range: 3 gear range L/M/Hi synchro Tractor speed: 40 km/h Minimum speed of tractor: 0.5 km/h
POWER TAKE-OFF	
Speed (dry disc clutch)	540/540e - 540/1000 rpm
Synchronised PTO	Optional for 24+24 / Standard for 24+12
HYDRAULIC SYSTEM	
Maximum lifting capacity	2600 kg (standard) / 3000 kg (optional)
Distributors	2 Distributors: 1 SE/DE SRN + 1 SE/DE SRN (4 rear outlets) with 2 pumps
Pump capacity	56.5+24.9 with 2 pumps (standard) / 56.5+24.9+26.2 with 3 pumps (optional)
THREE-POINT HITCH	
CAT 2 with lateral stabilisers	
DRIVER'S SEAT	
Tiltable front roll bar / Heated and air-conditioned cab	
WHEELS	
Front	320/70R20
Rear	480/65R28
DIMENSIONS	
Length (without ballast)	4078 mm
Height	2385 mm (cab) / 2533 mm (roll bar)
Wheelbase	2211 mm
Overall width (min/max)	1621 mm/2426 mm (Max. limit for circulation on roads: 2220 mm)
TABLE OF TYRE COMBINATIONS	
Front - rear wheels	320.70R20 - 480.65R28
	300.70R20 - 420.70R28
	320.70R20 - 420.70R28
	280.70R20 - 420.70R24
	280/70R20 - 380.70R28

Maximum width of tractor (metres)

1/1.1 1.1/1.2 1.2/1.3 1.3/1.4 1.4/1.5 1.5/1.6 1.6/1.7 1.7/1.8 1.8/1.9 1.9/2 2/2.1 2.1/2.2 2.2/2.3 2.3/2.4

V 80hp

VL 80/90/100hp

F 80/90/100hp

FL 100hp